



PRO35[®] EX3

CREATED BY P+S TECHNIK

Key Features



PRO35 for Sony PMW-EX3 delivery content

- ➔ Optimized for 35 mm film lenses – motion and still photography lenses
- ➔ Virtually the same depth-of-field, focus and angle-of-view as with a 35 mm film camera
- ➔ New designed relay lens projects the full 35mm image onto the triple chip CMOS sensor of the Sony PMW-EX3 camera
- ➔ Camera needs no modification; just mount the PRO35 and a 35 mm lens to your Sony PMW-EX3 camera
- ➔ MKII upgrade already included

Specifications

PRO35 EX3



PRO35 EX3 setup with camera

PRO35 camera mount (converter to camera)	Bayonet Mount
PRO35 lens mount (converter to lens)	PL Mount (standard)
Tuning for shooting sensor	Back focus
Frame position	Upright, Emulsion side up
PRO35's iris diaphragm (behind lens) (no effect on depth-of-focus)	Built-in for light reduction
Ground glass frequency, eccentric	Variable speed
Current consumption	300 mA / 12 V
Power supply	via battery holder
Length	208 mm
Weight	2500 gr. / 5.51 lbs
Best operating temperature	0 - 50° C

Order Information

Order No.	Article		
25088	PRO35 Image Converter for Sony PMW-EX3 incl. PL-Mount, lightweight support system for EX3, battery holder Sony NP-F with cable Note: With camera delivered mount adapter to Bayonet Mount needed	25652	Anton Bauer QR-EX3 Gold Mount for EX3
21422	Extension for handgrip for shoulder camera, 1p.	19142	PRO35 power supply cable AntonBauer 2pin
16528	Side handgrip	23504	Professional F Mount for PRO35
21423	Handgrip w/ ON/OFF switch and cable	19942	Nikon F Mount for PRO35
20449	RS switch ON/OFF	19940	Panavision Mount for PRO35
		20737	BNC-R Mount for PRO35
		20468	Canon EF Mount for PRO35
		22652	Canon FD Mount for PRO35
		20902	Zeiss-Contax Mount for PRO35