

## SI-2K LCD Touchscreen Monitor

The SI-2K LCD touchscreen monitor offers you comfortable and quick access to the operation menu of the SI-2K camera as well as a quality image to review your shot. The touchscreen lays all important menu options at just one finger tip away. Built from transfective panels and an anti-glare touchscreen, this monitor is still readable in direct sunlight. In addition an anti reflection surface coating minimises disturbing reflections on the monitor surface. The transfective panels redirect the direct sunlight to the back of the monitor surface and send it back as a passive reflection which helps to additional luminance of the display. The active VGA signal splitter integrated in the monitor offers a second VGA output, which is ideal for use with the SI-2K Electronic Viewfinder.



### Delivery content:

8,4" LCD touchscreen monitor with integrated active VGA splitter, power supply cable (#24660), VGA cable (#24659), USB cable (#24658), infrared remote control, touchscreen pen

### Technical Information

Measurements	232 x 162 x 75 mm / 9.13 x 6.38 x 2.95 inch
LCD Size	8.4"
Resolution	800 x 600
Aspect ratio	4:3
Brightness	450 nits or cd/m <sup>2</sup>
Certificates	CE certified
Power consumption	10 W

### Connections

Power input	12 V unbalanced, 5 V balanced, Lemo 4 pin
Power output	5 V / 12 V / +batt. (when connected to SI-2K Recording Unit) +batt (when connected to SI-2K Mini Rig battery holder)
Video input	VGA in
Video output	VGA out
Touchscreen control	USB (Type B)
Mechanical	1/4" thread hole for Noga arm (#23063, #24058)

### Order Information

Art.No.	Description	Art.No.	Description
24641	SI-2K Touchscreen LCD monitor 8,4"	24734	Sunshade for SI-2K Touchscreen monitor
<b>including</b>		23063	NOGA flex arm, 1/4" screw both sides
24658	USB cable for Touchscreen	24058	NOGA flex arm, 1/4" screw to rosette
24659	VGA cable Touchscreen to cam	24733	Power adapter cable for Touchscreen use with SI-2K Mini Rig, D-Tap to Lemo 4-pin
24660	Power supply cable for Touchscreen		