

CANON FD LENS REHOUSING

FULL FRAME CINE LENSES

P+S TECHNIK
Optics for Exceptional Images

This P+S TECHNIK rehousing transforms full frame Canon FD stills lenses into fully functional cine lenses. These fast lenses cover the full frame "VistaVision" format (24x36) and several focal lengths even cover RED 8K format (see also image circle charts).

The new housing includes new internal mechanics for focus and iris and standard PL mount. Exchange mounts are available.

Aperture and focus gear rings are in the same distance throughout the series. Focus rings are available in meter or feet.

Canon FD vs. Canon K35

The character of the Canon FD glass works very well with the Canon K35 lenses. In addition, all lenses are ready for the bigger "full frame" sensors. The best for last – FD glass are still available at reasonable prices.



WWW.PSTECHNIK.DE



Canon FD Lens Rehousing

Technical Specifications

Model	Canon FD L	Canon FD	Canon FD L	Canon FD SSC	Canon FD SSC	Canon FD	Canon FD SSC	Canon FD L	Canon FD	Canon FD	Canon FD	Canon FD	
Focal Length	14 mm f2.8	20 mm f2.8	24 mm f1.4	28 mm f2.0	35 mm f2.0	50 mm f1.4	55 mm f1.2	85 mm f1.2	85 mm f1.8	100 mm f2.0	135 mm f2.0	200 mm F2.8	
T-Stop	2,8–22	3,2–16	1,6–16	2–22	2–22	1,6–22	1,4–16	1,2–16	2–22	2–22	2,2–22	2,8–22	
Angular Rotation of Iris Scale	80°	55°	75°	~90°	~90°	~90°	~90°	~90°	~90°	80°	45°	75°	
Angular Rotation to MOD	250°	200°	250°	250°	250°	250°	250°	250°	250°	250°	250°	270°	
Image Circle	>36 mm		>36 mm	43 mm	43 mm		43 mm	43 mm	43 mm	>36 mm	>36 mm	>36 mm	
Mount	Arriflex PL-Mount, compatible with IMS exchange mounts												
Front Diameter	110 mm												
Weight	1.200 gr									1.500 gr		1.900 gr.	