

LEICA-R LENS REHOUSING

FULL FRAME CINE LENSES

This P+S TECHNIK rehousing transforms full frame Leica-R still photography lenses into fully functional cine lenses. The new housing includes new internal mechanics for focus and iris and standard PL mount. Exchange mounts are available. Aperture and focus gear rings are in the same distance throughout the series. Focus rings are available in meter or feet.

Rehousing is available for Summilux-R, Summicron-R and most Elmarit-R lenses.

P+S TECHNIK
Optics for Exceptional Images



WWW.PSTECHNIK.DE



Leica –R Lens Rehousing

Technical Specifications

Model	Elmarit-R	Elmarit-R	Elmarit-R	Elmarit-R	Makro-Elmarit-R	Apo-Makro-Elmarit-R	Summilux-R	Summilux-R	Summilux-R	Summicron-R	Summicron-R	Summicron-R	Apo-Summicron-R
Focal Length	19 mm f2.8	24 mm f2.8	28 mm f2.8	135 mm f2.8	60 mm f2.8	100 mm f2.8	35 mm f1.4	50 mm f1.4	80 mm f1.4	35 mm f2.0	50 mm f2.0	90 mm f2.0	180 mm f2.0
T-Stop	3.2	3.2	3.2	3.2			1.7	1.7	1.5				
Angular Rotation of Iris Scale	61°	43°	43°	44°		43°	61°	61°	65°	43°	43°	43°	
Close Focus	0,24 m / 7 in	0,3 m / 12 in	0,3 m / 12 in	1,5 m / 5 ft	0,7 m / 2,5 ft	0,7 m / 2,5 ft	0,46 m / 1 ft 6 in	0,46 m / 1 ft 6 in	6 m / 2 ft	0,3 m / 12 in	0,5 m / 20 in	0,7 m / 2,5 ft	
Angular Rotation to MOD	210°	250°	250°	250°	250°	250°	250°	250°	250°	250°	250°	250°	250°
Image Circle	43 mm	43 mm	43 mm	43 mm	43 mm	43 mm	43 mm	43 mm	43 mm	43 mm	43 mm	43 mm	43 mm
Mount	PL, IMS Interchangeable Mount System												
Front Diameter	110 mm												
Weight	1.000gr.	~1.100gr.	~1.100gr.	~1.500gr.			~1.500gr.	~1.300gr.	1.300gr.	~1.500gr.	~1.300gr.	~1.300gr.	