

Technical Specifications - PS-Rehousing Kowa Anamorphic				
	40mm	50mm	75mm	100mm
T-Stop Range	T2.3 /22	T2.3 /22	T2.8 /22	T3.4 /32
Angular Rotation Iris original Lens	100°	100°	100°	100°
Min. Marked Object Distance m / f	1m /3'	1,1m/ 3'	1,0m / 3'	1,7m / 5'
Close Focus from Lens Front	1m /3'	1,1m/ 3'	1,0m / 3'	1,7m / 5'
Angular Rotation to MOD Endstop	200°			
Image Circle	31,1mm	31,1mm	31,1mm	31,1mm
Length from Front of Lens to Lens Mount	95mm	105mm	134mm	164mm
Filter Thread	77mm			
Front Diameter	80mm			
Total Weight	1180gr	1300gr	1560gr	1760gr
Mount	Arriflex PL-Mount, compatible with IMS exchange mounts			
Focus Scales	metric or footage scales - two opposing focus scales with hard stop			
Markings	approx. 20 in m /ft			
Focus Drive Gear	teeth 0,8 metric module industrial standard,with hard stop, 90 mm from image plane			
Iris Scales	iris scales from Camera Operator side with hard stop			
Iris Drive Gear	teeth 0,8 metric module industrial standard,hard stops, 70 mm from image plane			
Additional Notes	*Image circle covers minimum Arri Alexa 4:3, for additional information also check our Image Circle Charts.			

Subject to technical change without notice.