KOWA ANAMORPHIC LENS REHOUSING

P+S TECHNIK
Optics for Exceptional Images

LIGHTWEIGHT AND SMALL

The KOWA Anamorphic lenses have been produced until the 1970's. They are rare and popular because of their compact form and light weight. A full lens rehousing for the classic 4 lens set – The KOWA Anamorphic 40mm, 50mm, 75mm, and 100mm is now available. With the KOWA Evolution lenses we add a wide angle and a 135mm.

With the new housing, fragile mechanics are replaced. In addition, the lenses are equipped with durable parts all while maintaining the original slim form and light weight. Therefore stability is maintained and ensured in today's production environments. Because of this, these lenses are far less prone to frequent service. The unique ability to replace broken or damaged lens elements with our close to original glass keeps your investment protected in these KOWA lenses.





KOWA Anamorphic Lens Rehousing

Technical Specifications

Focal Length 40 mm 50 mm 75 mm 100 mm T.Stop T2.4 / 22 T2.4 / 22 T2.8 / 22 T3.4 / 32 Angular Rotation of Iris Scale 95° 95° 85° 95° Close Focus 3' / 1 m 3' / 1,1 m 3' / 1,0 m 5' / 1,7 m Angular Rotation to MOD 250° 250° 250° 250° Image Circle 31,1 mm 31,1 mm 31,1 mm 31,1 mm Mount Standard Arriflex PL-Mount, compatible with IMS exchange mounts Front Diameter 80 mm	Model	Prominar Anamorphic			
Angular Rotation of Iris Scale 95° 95° 85° 95° Close Focus 3' / 1 m 3' / 1,1 m 3' / 1,0 m 5' / 1,7 m Angular Rotation to MOD 250° 250° 250° 250° Image Circle 31,1 mm 31,1 mm 31,1 mm 31,1 mm Mount Standard Arriflex PL-Mount, compatible with IMS exchange mounts Front Diameter 80 mm	Focal Length	40 mm	50 mm	75 mm	100 mm
Close Focus 3° / 1 m 3° / 1,1 m 3° / 1,0 m 5° / 1,7 m Angular Rotation to MOD 250° 250° 250° 250° Image Circle 31,1 mm 31,1 mm 31,1 mm 31,1 mm Mount Standard Arriflex PL-Mount, compatible with IMS exchange mounts Front Diameter 80 mm	T-Stop	T2.4 / 22	T2.4 / 22	T2.8 / 22	T3.4 / 32
Angular Rotation to MOD 250° 250° 250° 250° Image Circle 31,1 mm 31,1 mm 31,1 mm 31,1 mm Mount Standard Arriflex PL-Mount, compatible with IMS exchange mounts Front Diameter 80 mm	Angular Rotation of Iris Scale	95°	95°	85°	95°
Image Circle 31,1 mm 31,1 mm 31,1 mm 31,1 mm Mount Standard Arriflex PL-Mount, compatible with IMS exchange mounts Front Diameter 80 mm	Close Focus	3' / 1 m	3' / 1,1 m	3' / 1,0 m	5' / 1,7 m
Mount Standard Arriflex PL-Mount, compatible with IMS exchange mounts Front Diameter 80 mm	Angular Rotation to MOD	250°	250°	250°	250°
Front Diameter 80 mm	Image Circle	31,1 mm	31,1 mm	31,1 mm	31,1 mm
	Mount	Standard Arriflex PL-Mount, compatible with IMS exchange mounts			
Welsha 4500 m. 4500 m. 4700 m.	Front Diameter	80 mm			
veight 1500 gr 1500 gr 1700 gr 1800 gr	Weight	1500 gr	1500 gr	1700 gr	1800 gr