

Technical Specifications - PS-Rehousing Canon K-35

	18mm T1.5	18mm T2.8	24mm T1.5	35mm T1.3	55mm T1.3	85mm T1.4
Series	Canon K-35	Canon K-35	Canon K-35	Canon K-35	Canon K-35	Canon K-35
T-Stop Range	T1.5	T2.8	T1.5	T1.3	T1.3	T1.4
Angular Iris Rotation (as Original Lens)	85°	70°	85°	85°	75°	75°
Min. Marked Object Distance m / f	0,3 m / 12 in	0,16 m / 7 in	0,32 m / 1'	0,3 m / 12 in	0,6 m / 24 in	0,9 m / 3 ft
Close Focus from Lens Front	0,3 m / 12 in	0,16 m / 7 in	0,19 m / 8"	0,3 m / 12 in	0,6 m / 24 in	0,9 m / 3 ft
Angular Rotation to MOD Endstop	270°	270°	270°	270°	270°	270°
Image Diagonal <i>also review image circle charts</i>	43 mm	43 mm	43 mm	43 mm	43 mm	43 mm
Length from Front of Lens to Lens Mount	108mm	75mm	75mm	108mm	84mm	108mm
Front Diameter	110mm	110mm	110mm	110mm	110mm	110mm
Total Weight	1400gr.	1050gr.	1100 g	1500gr.	ca. 1200gr.	ca 1500gr.
Mount	Arriflex PL-Mount, compatible with IMS exchange mounts					
Focus Scales	metric or footage scales - two opposing focus scales with hard stop					
Markings	m:24 ft: 22	m:24 ft: 26	m:25 ft: 25	m:25 ft: 24	m:26 ft: 26	m:26 ft: 26
Focus Drive Gear	teeth 0,8 metric module industrial standard,with hard stop, 103,5 mm from image plane					
Iris Scales	iris scales from Camera Operator side with hard stop					
Iris Drive Gear	teeth 0,8 metric module industrial standard,hard stops, 72 mm from image plane					