

Lens Rehousing

CANON K35

The P+S rehousing transforms full frame Canon K35 stills lenses into fully functional cine lenses. The new housing includes new internal mechanics for focus and iris and standard PL mount. Exchange mounts are available.

Aperture and focus gear rings are in the same distance throughout the series. Focus rings are available in meter or feet. A Canon K35 lens set can be completed very well with the Canon FD focal lengths of 14mm, 100mm, 135mm and 200mm.

Six primes are available:

- Canon K35 18mm / T 1.5
- Canon K35 24mm / T 1.5
- Canon K35 35mm / T 1.3
- Canon K35 50mm / T 1.3
- Canon K35 55mm / T 1.3
- Canon K35 85mm / T 1.4



Technical Data

Focal Length	T-Stop	MOD (Min. Marked Object)		Weight		Image Circle	Front Diameter	Angular Rotation of Iris Scale	Angular Rotation to MOD End-stop
		m	ft	kg	lbs				
18mm	T 1.5	0,3	12"	1,4	3	43mm	110mm	85°	270°
24mm	T 1.5	0,3	12"	1,2	2,6	43mm	110mm	85°	270°
35mm	T 1.3	0,3	12"	1,6	3,5	43mm	110mm	85°	270°
50mm	T 1.3	0,5	20"	1,4	3	43mm	110mm	tbd	270°
55mm	T 1.3	0,6	24"	1,6	3,5	43mm	110mm	75°	270°
85mm	T 1.4	0,9	3'3"	1,6	3,5	43mm	110mm	75°	270°

Technical specifications are subject to change without notice

For further information contact P+S TECHNIK GmbH Feinmechanik,
Phone +49 89 45 09 82 30, Email sales@pstechnik.de, www.pstechnik.de

